



[Asus M4A785TD-V Evo](#)

R0

Socket AM3, Bus Speed 2600 MHz, Asus Motherboard, Memory Technology DDR3 (16 GB Max Supported RAM), 1066 / 1800 MHz Memory Frequency, Supported Processor AMD Athlon 64 X2 / AMD Athlon II X4 / AMD Phenom X4, 4 Memory Slots, Audio Chipset VIA VT1708S, LAN Chipset Realtek 8112L, On-board Video, 8 Audio Channels, 12 USB Ports, 2 SATA Headers... [more](#)

Technical details

General

USB 2.0 Ports: 12
Form Factor: ATX
LAN Chipset: Realtek 8112L
Audio Channels: 8
On-board Video: Yes
Audio Chipset: VIA VT1708S
HDMI: Yes

Processor

Processor Socket: Socket AM3
Supported Processor: AMD Phenom X4, AMD Phenom X2, AMD Athlon 64 X2, AMD Sempron, AMD Phenom, AMD Athlon X2, AMD Athlon, AMD Phenom X3, AMD Phenom II, AMD Athlon II X4
Bus Speed (FSB): 2600 MHz

Memory

Memory Frequency: 1066, 1800 MHz
Number of Memory Slots: 4
Memory Technology: DDR3
Max System Memory: 16 GB

Connectors

Number of Serial ATA Headers: 2
Number of IDE Headers: 1
Number of PCI Slots: 1
Number of PCI-Express x1 Slots: 2
Number of PCI-Express x16 Slots: 2